

Rotavators

Compact Models available; –
1m (TSZLL100), 1.3m (TSZLL130) & 1.5m (TSZLL150)




- Heavy duty side chain drive immersed in oil bath
- Moveable lift arm brackets so the machine can be semi-offset.
- Heavy Duty P.T.O
- 3 point linkage with cat 1 lift pins
- Heavy Duty Gearbox
- Parking stand
- Fitted skids with simple depth control
- 6 outwards turning blades per flange
- Heavy Duty safety door



Model	HP Required	Weight	Curved blades
TSZLL100	20 – 35	130kg	30
TSZLL130	20 – 35	158kg	36
TSZLL150	20 – 35	190kg	42

Medium duty Rotavators
1.8M (TSST180), 2.1M (TSST210)

- T6 driveshaft with slip clutch mechanism
- H.D Gear Drive immersed in an oil bath
- 6 outwards turning blades per flange
- Moveable lift arm brackets so the machine can be semi-offset
- Heavy duty 3 point linkage with Cat 2 pins
- Heavy duty rotor with long-life seal.
- Heavy duty skids with simple depth control
- Heavy Duty back door with double chain support
- Parking stand



Model	HP Required	Weight	Curved blades
TSST 180	35 – 60	380kg	42
TSST 210	35 – 60	400kg	48

Economy Rotavators



UL Details:

- Gear driven side transmission
- Series -4 PTO with slip clutch (610 mm cross to cross)
- Adjustable lower hitch brackets
- CE safety guards
- Powder coated
- Adjustable side depth skids
- Three-points hitch Cat. I

UH Details:

- Gear driven side transmission
- Series -6 PTO with slip clutch (660 mm cross to cross)
- Adjustable lower hitch brackets
- CE safety guards
- Powder coated
- Adjustable side depth skids
- Three-points hitch Cat. I and Cat. II

	Weight (kg)	Working Width (mm)	Total Width (mm)	HP	Cat Pins	Number Of Knives
UL 60	200	1500	1645	25	1	42
UH 84	450	2100	2282	50-65	1-2	54